

## d-c-fix® glass

## Product Description: Sun Protection Film metalized, self-adhesive

Description PET (Polyethylene terephthalate), metalized; with scratch resistant hard Material: coating Thickness: 45μm or 0,045mm Adhesive: acrylic adhesive transparent polyester film Backing: Rejection of direct heat radiation: 67% Light transmission: 31% UV protection: 99% Dimensions: roll: 92cm, 2m Packaging: Roll packed in a squared cardboard packaging with product window Packaging includes sun protection film, cutter, squeegee, instructions Languages: Packaging: DE, EN, FR, IT, CZ, NL, PL, RO, GR, TR Instructions in packaging: D, EN Instructions for download: FR, IT, CZ, NL, PL, RO, GR, TR Packing carton is labeled with art.no., EAN/barcode and quantity Packing unit: Number of rolls per carton ■ 4 pcs. per carton Shrinkage of the film: lengthwise: 0 % crosswise: 0 % Shrinkage in compound film-film:

Storage

Cool and dry at room temperature (23 °C  $\pm$  2 °C). Avoid direct sunlight. The temperature should not exceed 40 °C on a permanent basis.

0 %

The company Konrad Hornschuch AG is certified after DIN EN ISO 9001, VDA 6.1 and QS 9000. We are producer of high-quality products.

lengthwise and crosswise:

All statements are based on our current knowledge and experience. Due to the variety of possible influences when processing our products we suggest to carry out individual tests. A legally obligatory warranty of characteristics cannot be derived.

As of: February 2008

